

(Managing Automated Vehicles Enhances Network)

V2X for automated driving in urban environments

Michele Rondinone Hyundai Motor Europe Technical Center GmbH, Germany

> ETSI ITS Workshop 08.03.2018 Berlin, Germany





Commission

MAVEN is funded by the EC Horizon 2020 Research and Innovation Framework Programme, under Grant Agreement No. 690727

HMETC Electronic System Development / Michele Rondinone / 10.122.140.10 / 2019-06-21 18:56 / This document is not allowed to copy or distribute illegally as a information property of HMETC. If you violate this rule, you can be punished by policy of HMETC and related local law.

General Information

Duration

✓ 36 months (Sept '16 – Aug '19)

Funding

✓ ~3M€ under EC H2020 programme

Partners:

✓ From five countries: DE, NL, CZ, BE, UK



dφnnıq











Gemeente Helmond



Website

www.maven-its.eu





MAVEN is funded by the EC Horizon 2020 Research and Innovation Framework Programme, under Grant Agreement No. 690727

European Commission

Project summary

Assumption

Road infrastructure applications will still play a key role in future cooperative automated driving era

Main objective

□ Increasing traffic efficiency and safety in urban areas by exploiting automated driving

Approach

- V2X-assisted traffic management solutions for cooperative automated vehicles (CAVs) at signalized intersections and intersection corridors
- □ V2X-based automated driving extensions for perception and planning
- Use of simulation verification as well as real-road experiments with CAV and infra prototypes (ETSI ITS G5-based)



ommission



Use cases overview



I2V interactions

 V2I "explicit" probing + I2V speed/lane advisory + V2I feedbacks on compliance to advisories

Traffic controllers optimization

Signal optimization, priority management, queue estimation, green wave

Platoon management

- ✓ Forming, joining, travelling in, leaving, breaking a platoon
- Inclusion of conventional traffic and VRUs
 - Detection/reaction in presence of non-coop cars & VRUs





Commission

MAVEN I2V interactions



V2I explicit traffic probing (1)

MAVEN

000

CAVs and/or platoons transmits planned route, desired speed, platoon size, etc.

Traffic light controller signal timing re-optimization and I2V advisories (2)

- Based on rx info/calculations, infra transmits new speed /lane change advisories
- V2I feedbacks on compliance to advisories (3)
 - CAVs and/or platoons communicate if suggestion can be executed
 - If yes, traffic light controller "freezes" signal timing optimization

MAVEN is funded by the EC Horizon 2020 Research and Innovation Framework Programme, under Grant Agreement No. 690727



HMETC Electronic System Development / Michele Rondinone / 10.122.140.10 / 2019-06-21 18:56 / This document is not allowed to copy or distribute illegally as a information property of HMETC. If you violate this rule, you can be punished by policy of HMETC and related local law.

V2X for I2V interactions (1)



Ext CAM on SCH0	ItsPduHeader (as in [ETSI EN 302 637-2])					
	CoopAwareness	GenerationDeltaTime (as in [ETSI EN 302 637-2])				
		CAMParameters	BasicContainer (as in [ETSI EN 302 637-2], includes car position)			
			HighFrequency Container = BasicVehicleContainerHighFrequency (as in [ETSI EN 302 637-2], includes dynamic info)			
			LowFrequencyContainer = BasicVehicleContainerLowFrequency (as in [ETSI EN 302 637-2])			
			SpecialVehicleContainer = MavenAutomatedVehicleContainer			

Message for V2I traffic probing

- Backward-compatible extension of CAM (on Day1 SCH0)
- MavenAutomatedVehicleContainer includes info needed by TLC
 - CAV route at intersection (e.g. Ingress/egress lane)
 - Distance to preceding/following vehicle
 - Platoon id (tx by platoon leader if platoon is present)
 - ✓ Platoon participants (tx by platoon leader if platoon is present)
 - Desired platoon speed (tx by platoon leader if platoon is present)



Commission



V2X for I2V interactions (2)



	ItsPduHeader (as in [ETSI EN 302 637-2])
	MapData (as in ISO 19091 DSRC, profiled with lane-specific SignalGroups)
	ItsPduHeader (as in [ETSI EN 302 637-2])
	SPAT (as in ISO 19091 DSRC, profiled with lane-specific SignalGroups)
	ItsPduHeader (as in [ETSI EN 302 637-2])
MM	TimeInfo
	AM

LaneAdviceList

Messages for I2V advisories

- ✓ Lane-specific GLOSA
 - Suggests speed to be adopted on a given lane, calculated based on queue estimation
 - ✓ Use current standard SPATEM/MAPEM
 - SPATEM/MAPEM profiled to allocate lane-specific signal groups when needed (even if 2 or more lanes are logically associated to the same signal group)

L/ MA

- Lane advice message
 - Suggests the lane a CAVor platoon should change to at an intersection
 - Indicates target lane, distance to stop line, and time for starting the maneuver



Uses a newly defined Lane Advisory Message (LAM) including individual advices



European Commission

V2X for I2V interactions (3)



ItsPduHeader (as in [ETSI EN 302 637-2])				
CoopAwareness		GenerationDeltaTime (as in [ETSI EN 302 637-2])		
	AMParameters	BasicContainer (as in [ETSI EN 302 637-2], includes car position)		
		HighFrequency Container = BasicVehicleContainerHighFrequency (as in [ETSI EN 302 637-2], includes dynamic info)		
		LowFrequencyContainer = BasicVehicleContainerLowFrequency (as in [ETSI EN 302 637-2])		
	0	SpecialVehicleContainer = MavenAutomatedVehicleContainer		
	wai	CoopAwareness CAMParameters		

Message for V2I feedbacks on compliance to advisories (3)

- Backward compatible extension of CAM message (on Day1 SCH0)
- MavenAutomatedVehicleContainer includes feedback needed by TLC
 - Real-time Acknowledgment on whether the GLOSA is being applied by the CAV
 - Real-time Acknowledgment on whether the lane change is being executed by the CAV





Commission

MAVEN platooning





Mix between distributed and centralized approach

- Based on common distributed algorithm and V2V exchanged info, individual vehicles form platoons and manage their operation (joining, leaving, etc.) (1)
- Yet, platoon leader has the central role of communicating platoon features to the infra for explicit traffic probing (2)

Use of 2 parallel ITS G5 channels

- One for advertising vehicle and/or platoon characteristics to other vehicles or infra
- ✓ The other, to convey more frequent platoon control and management info



MAVEN is funded by the EC Horizon 2020 Research and Innovation Framework Programme, under Grant Agreement No. 690727



European Commission

V2X for MAVEN platooning



2	ItsPduHeader (as in [ETSI EN 302 637-2])				
	CoopAwareness		GenerationDeltaTime (as in [ETSI EN 302 637-2])		
5		CAMParameters	BasicContainer (as in [ETSI EN 302 637-2], includes car position)		
			HighFrequency Container = BasicVehicleContainerHighFrequency (as in [ETSI EN 302 637-2], includes dynamic info)		
			LowFrequencyContainer = BasicVehicleContainerLowFrequency (as in [ETSI EN 302 637-2])		
			SpecialVehicleContainer = MavenAutomatedVehicleContainer		



Message for platooning initialization

- Backward compatible extension of CAM message (on Day1 SCH0)
- MavenAutomatedVehicleContainer carries info for CAVs to detect opportunities for building/joining a platoon (e.g. Based on same expected route, desired speed, etc)

Message for platooning management and control

- Shorter CAM tx on a parallel SCH with higher frequency [10-30Hz]
- Carries limited set of info
 - for platoon control (e.g. Planned path, position, speed, acceleration, heading)
 - for platoon management: joining, brake-up, termination (e.g. flags representing the vehicle status in the platoon and used by the platoon logic)





European

Commission

Inclusion of conventional traffic and VRUs



□ Use of collective perception for improved detection and reaction

- ✓ Both CAVs and infra can detect and share info about non-cooperative road users
- ✓ Improved awareness used to adapt CAV maneuver/path planning for increased safety
- Isolated CAVs or CAVs in platoon keep monitoring the environment and control the system all the time to possibly undertake emergency (automated) reactions



Commission



V2X for inclusion of conventional traffic & VRUs



	ItsPduHeader (as in [ETSI EN 102 894-2])					
	u		GenerationDeltaTime (as in [ETSI EN 302 637-2])			
CPM	erception	eters	OriginatingStationContainer			
	CollectiveP	CPMParameters	SensorInformationContainer			
	Colle	CPMI	PerceivedObjectContainer			

Message for collective perception

- Adoption of Collective Perception Message (CPM) in pre-standardization at ETSI ITS (TR 103 562 and TS 103 324) and consideration at the C2C-CC
- Active contribution to ETSI CPM standardization to accommodate MAVEN requirements
 - General restructuring of CPM to accommodate detections from RSUs
 - Definitions based on RSU-specific reference system in all containers
 - ✓ Possibility to match detected objects to topological information transmitted in MAP messages



ANS.1 definitions for all presented messages and V2X solutions details soon availabe at:

www.maven-its.eu

Do not hesitate to contact us!

Thank you!

Questions?





Commission

MAVEN is funded by the EC Horizon 2020 Research and Innovation Framework Programme, under Grant Agreement No. 690727

HMETC Electronic System Development / Michele Rondinone / 10.122.140.10 / 2019-06-21 18:57 / This document is not allowed to copy or distribute illegally as a information property of HMETC. If you violate this rule, you can be punished by policy of HMETC and related local law.